

PROTECT YOUR PREMISES with Dunn & Farrugia's range of Security Fencing and Swing or Sliding Gates (Automation available). Pickets pass through punched rails then Silicone Bronze welded, top and bottom of rail for *maximum strength!* Manufactured in Pre-Gal or Hot Dipped Gal then Powder Coated or the option of

DuraBOND™ (Pre-Gal, Zinc Coated then

Powder Coated) for superior protection in harsh salt environments.



HEAVY SECURITY



CAPPED HEAVY SECURITY



REVERSE CRIMP ™
Aust. Reg. Design No. 150082



CRANKED SECURITY

*available in Crimp or Reverse Crimp panel heights nominal only



SPECIFICATIONS

PANELS

- 2.400m Wide x 1.800/2.100/2.400m High.
- <u>RAILS</u> 40 x 40sq x 1.6mm (punched and silicone bronze welded top and bottom).
- **VERTICALS** 25 x 25sq x 1.2mm.
- **SECURED WITH** Internal "L" Clips, Panel Mounts or High Security Fitting.
- FIXING Tek Screws or Rivets
- **POSTS** 65 x 65sq x 2.5mm.


- GATE
- Double bottom rail.
- **FRAME** Up to 4.000m 40 x 40sq x 1.6mm Above 4.000m - 65 x65sq x 2.5mm,

• Swing or Sliding (Automation available).


- HINGES Top -
- Broadbutt Hinge
- Ballbearing Hinge. (Heavy Duty Rollerbearing Hinges Recommended with 8.000m Gates and Larger)
- LOCKING with broadhurst slide bolt or chain.
- **POSTS** 100 x 100sq x 5mm.




BROADHURST SLIDE BOLT



INTERNAL "L"-CLIP



PANEL MOUNT



HIGH SECURITY
FITTING